



Prestige Product Code	:	CPBLOCK5KGBUFREG
Description	:	Extra Washed, Low eC, 5 Kg – treated with Calcium and Magnesium nitrates.
Sieve mesh size	:	6 mm (~1/4" inch)
Composition	:	Coco pith: 90%, Coco Fiber: 5-7%, Sand: 2-4%
Electrical Conductivity	:	< 0.5 mS/cm (Volume extract 1 : 1.5 Method) < 250 ppm (0.5 ppm scale)
Compression Ratio	:	5:1
Moisture (on Packing)	:	< 20%
pH	:	5.8 – 6.8
Calcium	:	6500-7250 ppm per BaCl ₂ test method.
Potassium	:	< 250 ppm per BaCl ₂ test method.
Sodium	:	< 60 ppm per BaCl ₂ test method.
Unit Dimensions	:	30 cm x 30 cm x 12-14 cm (12 in x 12 in x 5 in)
Units per Pallet	:	185-210
Unit Weight	:	4.5-5.0 Kg (10-11 Lbs.)
Pallet Weight (Net)	:	925-1050 Kgs (2000-2300 Lbs.)
Unit Hydration Capacity	:	16-20 Liters of water (4.25 – 5.25 Gallons)



3640 Walnut Grove Lane, Cumming, GA 30041 (USA)
Tel: +1-843-647-6363 Fax: +1-843-647-6364 helpdesk@prestige-impex.com



- Unit Yield on Hydration (Expansion) : 72-80 Liters (0.094 – 0.105 Cubic Yards)
- Pallet Yield on Hydration (Expansion) : 19 ¹/₄ to 21 ³/₄ Cubic Yards
- Pallets per 40 ft ocean container : 20(USA legal weight: 19.4 MT = 42,500 Lbs.)
- Prestige Product Code : CPBLOCK5KGBUFREG



3640 Walnut Grove Lane, Cumming, GA 30041 (USA)
Tel: +1-843-647-6363 Fax: +1-843-647-6364 helpdesk@prestige-impex.com